



A.B.N. 32 115 183 356

Office: 10 Harborne St, Macleod Victoria Australia 3085

Tel: 1300 768 976 or 61 (0) 425774988

Email: sales@abeve.com.au web: www.abeve.com.au

BOLONDI BARREL CLEANER

Water pressure driven barrel cleaner, eliminates the need for motors and electrical wiring. The gearing is all enclosed which reduces breakdowns and maintenance costs. A proven unit in Australia and New Zealand. There is a choice between 4 or 2 nozzle heads depending on the flow rate and pressure coming from the water unit.

Features:

- Water pressure driven rotating head.
- Stainless Rotating spray head with 4 or 2 nozzles.
- *Bolondi* offer 12 different nozzle diameters (0.9mm to 2mm) for their wash units.
- These nozzles can work with pressures from 10 to 150bar and water flow rates from 6 to 30 litres per minute.
- For example the nozzle model 1004 (4 nozzle) has a spray nozzle diameter of 1mm and works with a water pressure of 150bar @ 20 litres per minute or 120bar @ 18 litres per minute.
- A 4 nozzle cycle is 25 rotations with complete cycle time of only 66 seconds!
- Recommended cleaning time with hot water is 150 seconds (4 nozzle unit).
- Maximum temperature of the water is 90°C for standard unit (units on special request can be manufactured tolerant to 95°C)
- Barrel Cleaner has NBR seals and is supplied with an internal filter.
- Mounted on a custom design trolley for entry into the barrel when it is rotated having the bung hole at the bottom (6 o'clock position).
- High Pressure Wash Hose connected with s/steel elbows tolerant up to 150° Celsius; 400Bar/5800psi
- Nickel coated Brass high pressure DN 12 ball valve tolerant

