

New project for CO₂ value chain evaluation: Cement cArbon Storage Pilot for Emission Reduction (CASPER)

DTU Chemical Engineering

Randi Neerup, Juanita G. Dávila, Halil Halilov, Søren Jensen, Jakob L. Karlsson, Andreas B. Lunkeit, Quynh T. Nguyen, Laura M. Agneessens, Kate Harboe, Betina Jørgensen, Martin P. Haspang, Philip L. Fosbøl



CASPER

Funding: INNO-CCUS¹

Timeframe: 2023-2026

Total budget: DKK 14.6 million DKK

DTU budget: 10 million DKK

Main goal: Evaluate the whole CCS value chain

Project leader: Philip Loldrup Fosbøl, DTU CERE



Overall Project Objectives

The project will assess the feasibility of CCS for cement production by:

- Capturing and conditioning CO₂ from cement flue gas
- Measuring CO₂ quality and comparing it with relevant storage standards
- Evaluating the effect of impurities on CO₂ transport preparing for future infrastructure development



Aalborg Portland

- Produces 2.4 million tons cement per year
- Denmark's largest emitter of CO₂ accounting for 4% of DK's total emissions
- Emissions due to the chemical process of burning limestone
- 2030: capture up to 1.4 million tons CO₂ per year
- Captured CO₂ transported by pipeline to on-shore storage facility



Flue gas content

Flue gas data	Unit	Median	Emission limit (daily average)
Temperature	°C	132	-
CO ₂	Vol%, Wet	18-20	-
H ₂ O	Vol%, Wet	33.8	-
O ₂	Vol%, Wet	6.9	-
N ₂ + Ar	Vol%, Wet	46,3	-
CO	mg/Nm ^{3,*}	718	1500
SO ₂	mg/Nm ^{3,*}	0.9	50
HCl	mg/Nm ^{3,*}	0	10
NO _x **	mg/Nm ^{3,*}	268	500
NH ₃	mg/Nm ^{3,*}	20.0	30
TOC	mg/Nm ^{3,*}	5	10
Dust***	mg/Nm ^{3,*}	9.5	20

*dry @ 10% oxygen, 1013 hPa, dry, 0 °C

**NO_x is assumed to be 94% NO, 5% NO₂ and 1% N₂O

*** Filter trips occur with typical frequency of 1 per week with duration of app. 1 min

Installation Aalborg Portland, Denmark




Mobile CO₂ capture plant

- Designed by the Technical University of Denmark and Pentair Union Engineering
- Constructed by Pentair Union Engineering
- Absorber: 19.36 m
- Stripper: 17.54 m
- Packing material: random Flexiring 5/8 inch, 316 (Koch-Glitsch)
- Exhaust gas flow rate: 145 kg/h
- More than **20 advanced configurations**:
 - Lean vapor compression (LVC)
 - Rich and lean solvent recycle
 - Intercooling (IC)
 - Cold rich solvent split (CRSS)



Mobile CO₂ capture plant

- CO₂ product recycle
- Depleted flue gas recycle
- Cold rich solvent split (CRSS)
- Intercooling (IC)
- Rich solvent recycle (RR)
- Lean vapour compression (LVC)




Liquefaction unit & storage

- Liquefaction unit: Dalum Beverage Equipment
 - Production: 0-18 kg/h liquid CO₂
 - Delivers > 99.9% pure CO₂
 - Pressure: up to 46 bar (delivers 15 bar)
- CO₂ storage tank:
 - Capacity: 950 L (1070 kg CO₂)
 - Design temperature: -196 °C
 - Operation: 15 bar, -30 °C



CO₂ liquefaction unit



Commissioning - filter




Old filter




New filter

Commissioning – cooler



Commissioning – critical components



Heat loss



HE malfunction

CESAR1 formulation

CESAR1 formulation:
27 wt% AMP and 13 wt% PZ




Modified CESAR1 formulation:
26 wt% AMP and 6 wt% PZ




Performance of process configuration

- Lean Vapour Compression (LVC): 42% energy reduction




Pilot-scale CO₂ capture in a cement plant with CESAR1: Comparative analysis of specific energy consumption




Pilot-scale CO₂ capture in a cement plant with CESAR1: Higher stripper pressure reduces energy demand and compression work but increases solvent degradation

Isaac Appelquist Løge^{a,b,*}, Can Demir^{a,b}, Sai Hema Bhavya Vinjarapu^{a,b}, Randi Neerup^{a,b}, Ebbe Hauge Jensen^b, Jens Kristian Jørsboe^{a,b}, Maria Dimitriadis^{a,b}, Vanja Buvik^c, Halil Halilov^c, Carsten Fritzner Frøstrup^{a,b}, Istvan Gyorbíró^{a,b}, Nomiki Kottaki^a, Asams Nelliparambil Jayan^c, Søren Jensen^d, Jakob Lindkvist Karlsson^d, Philip Loldrup Fosbøl^{a,b}

Solvent degradation & emissions



Solvent emission from Aalborg Portland




Separation and Purification Technology

Volume 374, 28 November 2025, 133693



Pilot-Scale CO₂ capture in a cement plant with CESAR1: Emission control with acid wash and absorber intercooling

Maria Dimitriadi ^a , Isaac Appelquist Løge ^a, Randi Neerup ^a, Søren Jensen ^b, Jakob Lindkvist Karlsson ^b, Lars Piilmann Brorholt ^c, Frantz Bræstrup ^c, Halil Halilov ^d, Sebastian Nis Bay Villadsen ^a, Jens Abildskov ^e, Philip Loldrup Fosbøl ^a



- Reduction of Ammonia levels
- Change in pH
- No effect with circulation changes

Solvent degradation from Aalborg Portland campaign



Chemical Engineering Journal





Volume 510, 15 April 2025, 161542



CO₂ capture pilot campaign: Understanding solvent degradation of CESAR1 in cement plant operations

Randi Neerup ^a, Kalle L. Øbro ^a, Isaac A. Løge ^a, Nomiki Kottaki ^a,
Carsten F. Frøstrup ^a, Istvan Gyorbíró ^a, Maria Dimitriadí ^a, Halil Halilov ^b,
Søren Jensen ^c, Jakob L. Karlsson ^c, Philip L. Fosbøl ^a

• Lean • Rich



PCCC-8, Marceille 16-09-2025

Upcoming events

- Measuring campaign, autumn 2025
 - DTU: Gasmeter FTIR (CO₂)
 - DTU: Protea FTIR (flue gas, depleted flue gas)
 - Evida: (CO₂)
 - DTI: TOF-MS (flue gas, depleted flue gas)

- Optimization campaign
 - End 2025 to early 2026

- Expected end: winter 2026

- CO₂ utilization:
 - Contact DTU: plf@kt.dtu.dk and rand@kt.dtu.dk



Acknowledgement

The financial support from the Cement cARbon Storage Pilot for Emission Reduction project (INNO-CCUS Pool2: 1-P8 CASPER)



INNO-CCUS
Carbon capture,
utilisation and storage

Thanks to the project partners:



Thank you for listening

More information: Philip L. Fosbøl, plf@kt.dtu.dk & Randi Neerup, rand@kt.dtu.dk